

KARDEN NAVICARE

PRODUCT CODE: KBK 02035
ANTIFOULING PAINT

**1. DESCRIPTION OF PRODUCT AND THE PRODUCER**

GENERIC TYPE	Self polishing type antifouling paint
DESCRIPTION, AREAS OF USE	One pack antifouling paint based on specially developed and well balanced binder-biocide technology. Provides mid-term protection against marine organisms at saltwater and fresh water environments.
PRODUCER INFORMATION	Kartallar Boya ve Kimya Sanayi Ticaret Limited Sirketi Koslucesme Mahallesi, Yeni Bagdat Caddesi, No:136, 41400 Gebze / KOCAELI / TURKIYE
PRODUCT HOTLINE	Monday-Saturday (08:30 - 18:00) Tel: 0262 641 49 67 Fax : 0262 641 49 68
EMERGENCY LINE	Uludag University Poison Research Center (7/24) - +90 224 442 82 93

2. PRODUCT'S TECHNICAL & APPLICATION PARAMETERS

COLOUR(S) / TEXTURE	Red, RedBrown, Black, Green, Blue
APPEARANCE	Matte
SPECIFIC GRAVITY	1,78±0,02g/cm ³ (ASTM D 1475)
SOLID BY VOLUME	%54±1 (ASTM D 2697)
THINNER CODE	No thinning required
THINNING RATE	N/A
VOC CONTENT	329 g/L (ASTM D 3960)
SPREADING RATE	8,5 sqm per liter when applied as single coat (100 microns DFT)
SURFACE DRY TIME	15- 20 minutes @20 °C
THROUGH DRY	2-3 hours @20 °C
READY FOR IMMERSION	12 hours @20 °C, Maximum time of immersion after applications: 6 months.
HARDENER TYPE - RATIOS	N/A
METHOD OF APPLICATION	Airless Spray, HVLP Spray, lint free roller, brush
NOZZLE INFO	0,023" - 0,031"
AIRLESS PUMP RATIO	45:1
SPRAY HOSE LENGHT	Maximum 20m with 45:1 pumps
PRESSURE INFO	180-220 bars
RECOMMENDED WET THICKNESS	145 microns
DRY FILM THICKNESS	80 microns
MINIMUM RECOATING INTERVAL	6 hours @20 °C
MAXIMUM RECOATING INERVAL	4 months @20 °C. If contaminated; clean surface by high pressure fresh water
POT LIFE	N/A
SHELF LIFE	18 months from the date of manufacture if stored at proper conditions and unopened

3. SURFACE PREPARATION & ENVIRONMENTAL CONDITIONS DURING APPLICATION

NEW APPLICATION	Oil and grease should be removed by a suitable detergent and this procedure should be followed by high pressure fresh water cleaning. Steel surfaces should be properly primed by a suitable KBK Marine primer and Tiecoat soon after completion of SA2 ^{1/2} blasting. Surface must be clean, dry and free from any contaminants. For aluminium hulls: at least 2 coats of recommended priming system should be applied.
REPAIRS	Corroded areas should be blast cleaned to ISO-Sa2 ^{1/2} . Existing paints should be dry and free from loose paints, salts, grease and other contaminants prior to overcoating. Leached layers of former antifouling paint should be removed by high pressure fresh water cleaning.
SURFACE SALT LIMITS	35µg/sqm
IMPORTANT NOTICES	This product contains heavy particles. Achieving the best performance from the product depends on stirring well and being sure that a homogeneous state is obtained.

DATE OF ISSUE : 21.09.2018

**KARTALLAR BOYA VE KIMYA SANAYI TICARET LIMITED SIRKETI**

Address : Koslucesme Mahallesi, Yeni Bagdat Caddesi, No:136, 41400- Gebze/ Kocaeli /TURKIYE
Tel: +90 262 641 49 67 E-mail : info@kartallarboya.com Website : www.kartallarboya.com

KARDEN NAVICARE

PRODUCT CODE: KBK 02035
ANTIFOULING PAINT

**3. SURFACE PREPARATION & ENVIRONMENTAL CONDITIONS DURING APPLICATION (CONTINUED)****ENVIRONMENT CONDITIONS**

The temperature of the surface should be at least 3°C higher than the DewPoint of the air. Temperature and relative humidity should be measured in the vicinity of the substrate. The maximum recommended surface temperature is 40°C. In extreme cases, it may be necessary to reduce film thickness in order to avoid sagging. When applying the paint in confined spaces, provide adequate ventilation during application and drying. The temperature of the mixed paint should be at least 15°C. Otherwise extra solvent may be needed to obtain a proper application viscosity. Relative humidity must not be over %80

4. PACKING & STORAGE CONDITIONS**PACKING DETAILS**

4L and 20L steel containers

STORAGE CONDITIONS

Storing areas should be dry and well ventilated where the temperature is always between 5-30°C. These areas should be separated from the manufacturing fields to eliminate the risks of fire.

5. ENVIRONMENTAL RESPONSIBILITY, HEALTH & SAFETY**GENERAL RULES**

Observe the precautionary notices on the label of the container. A material safety data sheet is available upon request and national or local safety regulations should be followed. This product is intended for use by professional applicators.

HEALTH

Avoid skin- and eye contact by wearing overalls, gloves, goggles, mask, etc. Spillage on the skin should immediately be removed by thorough washing with lukewarm water and soap or a suitable industrial cleaner. Eyes should be flushed with fresh water and medical attention sought immediately. Spraying should be carried out under well-ventilated conditions. Avoid inhalation of solvent vapors and paint mist by wearing an air mask.

SAFETY

This product contains flammable materials and should be kept away from sparks and open flames. Smoking in the area should not be permitted.

6. DISCLAIMER**DISCLAIMER**

The information in this data sheet is provided to the best of our knowledge. However, we have no control over either quality or condition of the substrate and other factors affecting the use and application of this product. Therefore, we cannot accept any liability whatsoever or howsoever arising from the performance of the product or for any loss or damage arising from the use of this product. We reserve the right to change the product without notice.

DATE OF ISSUE : 21.09.2018

**KARTALLAR BOYA VE KIMYA SANAYI TICARET LIMITED SIRKETI**

Address : Koslucesme Mahallesi, Yeni Bagdat Caddesi, No:136, 41400- Gebze/ Kocaeli /TURKIYE
Tel : +90 262 641 49 67 E-mail : info@kartallarboya.com Website : www.kartallarboya.com